



Compatible
Compact
Ergonomic

Sliding optical
patch panels

Ergonomic

The sliding mounting plate and snap-on lid make easier inspection and connection (protection of connectors and pigtails)

Compact

Reduced depth and compact design: Drawers can be mounted back-to-back in 2 columns within a 19" rack (600 x 600 mm)

Can receive up to 4 cables, and be wired from the left and/or the right

Compatible

The BCCO II range of optical cable heads is compatible with two rack support standards:

- 19" • ETSI

Associated equipment

Fixed and sliding jumper storage drawer, follows the movement of the cable terminal during opening and closing, thus avoiding disturbing the coiled jumpers

Services

The cable terminals are pre-connectorized in the factory for simpler, safer site connection

Description



Body

- Monoblock for 19" or ETSI rack assembly
- Lateral cable inlets (parallel with the front face) on each side
- Allows the attachment of 4 cables (less than 8 mm diameter) on each side using rilsan clamps (6 supplied)
- Allows the attachment of a single cable (less than 18 mm diameter) on each side using serflex clamps (not supplied)
- 15/10 XC gauge steel plate 7016 RAL epoxy finish

Slides

- Made of anodised aluminium (factory lubricated) allowing the mounting plate to slide within the body

Mounting plate

- Monoblock, sliding mounting plate with integrated connecting strip
- 15/10 XC gauge steel plate 7016 RAL epoxy finish
- Fibre guides
- 2 handles for opening and closing
- 1 adhesive polycarbonate connector identification label with white inscriptions on 7016 RAL background
- 1 U version fitted with 2 hinged trays (4 trays in 2 U version) attached by means of rivets and fitted with standard splice supports

Cover

- 10/10 XC gauge steel plate 7016 RAL epoxy finish
- Positioned on the body and attached by the customer using supplied rivets; protects the fibres against possible external attack

Other items supplied

- 1 corrugated jacket allowing bare fibres or microstructures to be run between the body and the sliding mounting plate
- Attachment kit (screws, washers, captive nuts) for installation in the rack
- 1 set of installation instructions

■ **Capacity** • 12 to 24 fibres on 1 U • 36 to 48 fibres on 2 U

■ **Connection** • ST, FC, EC, SC and E2000 connector types as standard • Other connectors: contact us

19" Compatibility

Sliding patch panel with integrated trays for 19" rack standard

■ 1 U for 12 ST, FC	BCCO II	N461580A0000
■ 1 U for 12 SC, E2000, EC	BCCO II	N461592A0000
■ 1 U for 24 ST, FC	BCCO II	N461529A0000
■ 1 U for 24 SC, E2000, EC	BCCO II	N461554A0000
■ 2 U for 36 ST, FC	BCCO II	N461559A0000
■ 2 U for 36 SC, E2000, EC	BCCO II	N461593A0000
■ 2 U for 48 ST, FC	BCCO II	N461582A0000
■ 2 U for 48 EC/SC	BCCO II	N461555A0000

Sliding storage drawer for 19" rack standard

■ 1U with management of over lengths	BCCO II	N461571A0000
■ 1U without management of over lengths	BCCO II	N461572A0000

Splicing drawer (flat front face) for 19" rack standard

■ 24 fibre splicing drawer	BCCO II	N461596A0000
■ 48 fibre splicing drawer	BCCO II	N461560A0000

Dimensions

1 U 19" = 487 mm x 240 mm x 44 mm, fixed pull-out length of 40 mm

2 U 19" = 487 mm x 240 mm x 88 mm, fixed pull-out length of 40 mm

Packaging

1 U cable terminal for 19" rack standard
Type: cardboard box • Weight: 4 kg.
Dimensions: 500 x 240 x 44 mm

2 U cable terminal for 19" rack standard
Type: cardboard box • Weight: 5 kg.
Dimensions: 500 x 240 x 88 mm

Storage drawer for 19" rack standard
Type: cardboard box • Weight: 3.6 kg
Dimensions: 500 x 215 x 58 mm

ETSI Compatibility

Sliding patch panel with integrated trays for ETSI rack standard

■ 1 U for 24 ST, FC	BCCO II	N461594A0000
■ 1 U for 24 SC, E2000, EC	BCCO II	N461530A0000
■ 2 U for 48 ST, FC	BCCO II	N461595A0000
■ 2 U for 48 SC, E2000, EC	BCCO II	N461570A0000

Sliding storage drawer for ETSI rack standard

■ 1U with management of over lengths	BCCO II	N461573A0000
■ 1U without management of over lengths	BCCO II	N461574A0000

Splicing drawer (flat front face) ETSI rack standard

■ 24 fibre splicing drawer	BCCO II	N461597A0000
■ 48 fibre splicing drawer	BCCO II	N461598A0000

Dimensions

1 U ETSI = 532 mm x 240 mm x 48.7 mm, fixed pull-out length of 40 mm

2 U ETSI = 532 mm x 240 mm x 98.7 mm, fixed pull-out length of 40 mm

Packaging

1 U cable terminal for ETSI rack standard
Type: cardboard box • Weight: 4.5 kg
Dimensions: 545 x 240 x 49 mm

2 U cable terminal for ETSI rack standard
Type: cardboard box • Weight: 4 kg
Dimensions: 545 x 240 x 99 mm

Storage drawer for ETSI rack standard
Type: cardboard box • Weight: 4 kg
Dimensions: 545 x 215 x 59 mm

3, rue du Pont des Halles
Bât. A - Zone du Delta
94656 Rungis Cedex
Tel.: +33 (0)1 56 30 88 88 - Fax: +33 (0)1 46 87 29 87
Email: contact@pouyet.com
Web: www.quante-pouyet.com

New
address